

Fibrescan is a simple and reliable system for removal of colour PP contaminants in cotton Blowroom lines.

Multiple miniature camera array sensors interlaced with advanced technology are at the core of FibreScan.

- * DIPT (Digital Image Processing Technology)
- * PMAC (Pixel Mapping Across Camera Sensors)

- Day light for Colour Scanning

DIPT, PMAC in combination enhance the effectiveness of the equipment and provide the best efficiency among this technology machines in the world.

Features:

- * Multi-Camera Sensor one for every 65mm of duct width.
- * DIPT - Digital Image Processing Technology for optimum detection of Contaminants.
- * Very low clean cotton ejections typically 0.3% for 30 Ejections/Min.
- * Hybrid Embedded Controller enhances reliability.
- * Easy to clean and Maintain, No PC Needed.



Foreign Fibre Control Chamber

www.aaspl.net

Feed Option - Bottom to Top



Feed Option - Top to Bottom



Technical Specifications

Description	FibreScan Sapphire - Colour
Sensing Technology	Multiple Tech with Daylight Camera Array Sensing
Processing	Embedded Controller with DIPT – Digital Image Processing Technology PMAC – Pixel Mapping Across Camera Sensor Array
Type and No of Cameras	Multiple Camera Array Sensors - 32 Nos MonoChrome Daylight Camera Array Sensor
Resolution	2048*1 with 128 pixels for each camera
Camera scanning speed (LPS)	upto 12000 LPS for Camera Sensor Array
Production Capacity	800 Kgs /Hour
Throughput Duct size	1040 * 100 mm
Size of Machine	1250 x 500 mm Height will vary depends upon the blowroom layout
No of Ejection Value	26 Nos
Ejection Waste %	Below 0.3 % - 0.5 % Maximum 30 Ejection / Min
Sensitivity setting	On Area, Vertical, Horizontal Sizes & Size Wise Color selection Settings
Diagnostics	Camera Sensor, Ejection Valve, Lighting Hours, Intensity and - colour Performance graphs
Display Features	Comprehensive for Camera Array Sensor
Tube Light Nos and Wattage	6 Nos (3*2 - 54 Watts) fluorescent day light
Control System	Dedicated Embedded controller
Operator Interface	HMI and Console on Mc
Power consumption	1 Kw + Fan
Power	415 Volts 3 Phase 50 Hz
Ejected material Collection	AEMCH – Applied Ejected Material Collection Hanger – Optional
Booster Fan for Ejected Material	Booster Fan based on Feed Machine Specs
Ejected Cotton Grams/ Ejection	0.5 Grams / Ejection after Fine Cleaner 0.9 Grams / Ejection after coarse Cleaner
Compressed Air Requirements	3 CFM based on 40 Ejection/Min @ 6.5 Bar

* Trademark/Copyright patent rights of all products mentioned by name vest with respective manufacturers
 * Product specifications subject to change without notice due to continuous improvements

www.aaspl.net

APPLIED

Applied Automation Systems Private Limited
 SF No 415, Codissia Road, Peelamedu Coimbatore - 641 004 India
 Mobile : +91 9443033017, +91 9443033017
 sales.tex@aaspl.net
 www.aaspl.net

